



## Specifications

Printing System:	Single-Sided 300dpi, 24-bit continuous tone printing, 16.7million colors
Printing Method:	Thermal transfer dye-sublimation
Print Media:	PVC or polyester cards with polished PVC finish
Media Size:	CR-80: 3.375" x 2.125" / 85.6 x 54mm
Media Thickness:	30mil
Print Area:	Single-Sided Edge-to-Edge
Input Hopper:	100 cards
Exit hopper:	30 cards
Image Memory:	16MB with parallel processing, four memory modes
System Memory:	2.25MB
Display:	First ever rotating LCD 16 Character 2-line display shows printer status and diagnostic prompts
Ribbon Types:	YMCK 250 prints, K 1250 prints, & BK/OP 250 prints
* Print Speed:	YMCKO: less than 144 cards / hour
Interface:	USB 2.0
Dimensions:	7" (h) x 9" (w) x 13" (d), 180MM x 329MM x 222MM
Weight:	14lbs. / 6.5 kg
MTFB:	20,000 prints
Operating Temp:	10 to 35°C, 35-85%RH/without condensing
Power source:	AC power source AC100/240v 50/60Hz auto-switching
Agency Listing:	UL: UL1950: UL1950-1993 CE Class B FCC A & B
Drivers:	Windows Compatible
Warranty:	2-Year Hotswop.

HID and ICLASS are registered trademarks of HID Corporation. Other brands and names contained in this release are the property of their respective owners.